
DATE	CHANGES	REV
07.15.08	Original	1.00

DT-810



KEY SWITCH

MATERIAL: Industrial Silicone Rubber
LIFE: Greater Than 10 Million Cycles
TRAVEL: 0.055 in.
ACTUATION FORCE: 7.05 oz. +/- 1.06oz (200g +/- 30g)
FEEDBACK: Tactile with Mechanical Snap

POWER

PS2: KEYBOARD: 50mA@5V (from Keyboard port)
POINTER: 35mA@5V (from Mouse port)
USB: 85mA@5V (from CPU port)

TEMPERATURE RANGE

STORAGE: -40°F to +158°F (-40°C to +70°C)
OPERATING: -4°F to +140°F (-20°C to +60°C)

HUMIDITY

100% Humidity Resistant

ENCLOSURE CASE: Stainless Steel

VIBRATION

POWER SPECTRAL DENSITY: .04g/HZ
FREQUENCY RANGE: 20Hz-2Khz
DURATION OF TEST PER AXIS: 3 hours

SHOCK

3 X 11 ms pulses of 50g on each of 3 axis

WEIGHT

3.75 lbs +/- 0.10 lbs (1.70 kg +/- 0.05 kg)

PROPRIETARY / CONFIDNETIAL

SCALE: 1:2

iKey, Ltd.
2621 Ridgpoint Dr. Suite 235
Austin, Texas 78754
Voice: (512) 837-0283
Fax: (512) 927-8530
©2008 iKey,Ltd.

Part Number: DT-810	Drawing Number: MKT0115	Sheet: 1 OF 1	
Drawing Title: DT-810-MKT	Revision: 1.00	Date: 07.15.08	JWB