
DATE	CHANGES	REV
07.02.08	Original	1.00

RDC-1000



iKey, Ltd.
2621 Ridgpoint Dr. Suite 235
Austin, Texas 78754
Voice: (512) 837-0283
Fax: (512) 927-8530

©2008 iKey,Ltd.

Part Number: RDC-1000	Drawing Number: MKT0110	Sheet: 1 OF 2	
Drawing Title: RDC-1000-MKT	Revision: 1.00	Date: 07.02.08	JWB

RDC-1000

KEY SWITCH

MATERIAL: Industrial Silicone Rubber
LIFE: Greater Than 10 Million Cycles
TRAVEL: 0.055 in.
ACTUATION FORCE: 7.03 oz. +/- 0.70 oz (200g +/- 20g)
FEEDBACK: Tactile with Mechanical Snap

POWER

PS2: KEYBOARD: 40mA@5V (from Keyboard port)
USB: 40mA@5V (from CPU port)

TEMPERATURE RANGE

STORAGE: -40°F to +194°F (-40°C to +90°C)
OPERATING: 40°F to +158°F (-40°C to +70°C)

HUMIDITY

100% Humidity Resistant

VIBRATION

POWER SPECTRAL DENSITY: .04g/HZ
FREQUENCY RANGE: 20Hz-2Khz
DURATION OF TEST PER AXIS: 3 hours

SHOCK

3 X 11 ms pulses of 50g on each of 3 axis

WEIGHT

12.50 lbs +/- 0.10 lbs (5.67 kg +/- 0.05 kg)

iKey, Ltd.
2621 Ridgpoint Dr. Suite 235
Austin, Texas 78754
Voice: (512) 837-0283
Fax: (512) 927-8530
©2008 iKey,Ltd.

Part Number: RDC-1000	Drawing Number: MKT0110	Sheet: 2 OF 2	
Drawing Title: RDC-1000-MKT	Revision: 1.00	Date: 07.02.08	JWB