


SK-79-M

DATE	CHANGES	INTL	REV
08.31.04	Original		1.0
11.21.08	Updated Format	JB	1.0
06.25.09	Updated Dimension Accuracy	JB	2.0



KEY SWITCH

MATERIAL: Industrial Silicone Rubber
LIFE: Greater Than 10 Million Cycles
TRAVEL: 0.055 in.
ACTUATION FORCE: 4.76 oz. +/- 1.06oz (135g +/- 30g)
FEEDBACK: Tactile with Mechanical Snap

TEMPERATURE RANGE

STORAGE: -40°F to +158°F (-40°C to +70°C)
OPERATING: -4°F to +140°F (-20°C to +60°C)

VIBRATION

POWER SPECTRAL DENSITY: .04g²/HZ
FREQUENCY RANGE: 20Hz-2Khz
DURATION OF TEST PER AXIS: 3 hours

POWER

PS2:
KEYBOARD: 50mA@5V (from Keyboard port)
POINTER: 35mA@5V (from Mouse port)
USB: 85mA@5V (from CPU port)

HUMIDITY

100% Humidity Resistant

SHOCK

3 X 11 ms pulses of 50g on each of 3 axis

WEIGHT

1.00 lbs +/- 0.10 lbs (0.45 kg +/- 0.05 kg)

PROPRIETARY AND CONFIDENTIAL

SCALE: 1:1.5



iKey, Ltd.
 2621 Ridgpoint Dr. Suite 235
 Austin, Texas 78754

©2008 iKey, Ltd.
 Voice: (512) 937-0283
 Fax: (512) 927-9530

Part Number: SK-79-M

Drawing Title: SK-79-M-MKT

Drawing Number: MKT0034


Revision: 2.0

Sheet: 1 OF 2

Date: 06.25.09

JWB

SK-79-M BACK / MOUNTING



ENCLOSURE CASE: ABS/Polycarbonate

PROPRIETARY AND CONFIDENTIAL

SCALE: 1:1.5



iKey, Ltd.
2621 Ridgpoint Dr. Suite 235
Austin, Texas 78754

©2008 iKey, Ltd.

Voice: (512) 937-0283
Fax: (512) 927-8630

Part Number: SK-79-M

Drawing Title: SK-79-M-MKT

Drawing Number: MKT0034

Revision: 2.0

Sheet: 2 OF 2

Date: 06.25.09

JWB