

SLK-79-M

DATE	CHANGES	INTL	REV
11.21.08	Original	JB	1.0
06.25.09	Updated Dimension Accuracy	JB	2.0





KEY SWITCH

MATERIAL: Industrial Silicone Rubber
LIFE: Greater Than 10 Million Cycles
TRAVEL: 0.055 in.
ACTUATION FORCE: 4.76 oz. +/- 1.06oz (135g +/- 30g)
FEEDBACK: Tactile with Mechanical Snap

POWER

PS2:
KEYBOARD: 200mA@5V (from Keyboard port)
POINTER: 35mA@5V (from Mouse port)
USB: 235mA@5V (from CPU port)

TEMPERATURE RANGE

STORAGE: -40°F to +158°F (-40°C to +70°C)
OPERATING: -4°F to +140°F (-20°C to +60°C)

HUMIDITY

100% Humidity Resistant

VIBRATION

POWER SPECTRAL DENSITY: .04g²/HZ
FREQUENCY RANGE: 20Hz-2Khz
DURATION OF TEST PER AXIS: 3 hours

SHOCK

3 X 11 ms pulses of 50g on each of 3 axis

WEIGHT

1.00 lbs +/- 0.10 lbs (0.45 kg +/- 0.05 kg)

PROPRIETARY AND CONFIDENTIAL


SCALE: 1:1.5

iKey, Ltd.
2621 Ridgpoint Dr. Suite 235
Austin, Texas 78754
Voice: (512) 837-0283
Fax: (512) 927-8530

©2009 iKey,Ltd.

Part Number: SLK-79-M	Drawing Number: MKT0155	Sheet: 1 OF 2	
Drawing Title: SLK-79-M-MKT	Revision: 2.0	Date: 06.25.09	JWB

SLK-79-M BACK / MOUNTING



ENCLOSURE CASE: ABS/Polycarbonate

PROPRIETARY AND CONFIDENTIAL

SCALE: 1:1.5

iKey, Ltd.
2621 Ridgpoint Dr. Suite 235
Austin, Texas 78754
Voice: (512) 837-0283
Fax: (512) 927-8530
©2009 iKey,Ltd.

Part Number: SLK-79-M	Drawing Number: MKT0155	Sheet: 2 OF 2	
Drawing Title: SLK-79-M-MKT	Revision: 2.0	Date: 06.25.09	JWB