


# SLP-86-911

DATE	CHANGES	INTL	REV
04.01.08	Original		1.00
12.09.08	Updated Format	JB	1.00



## KEY SWITCH

**MATERIAL:** Industrial Silicone Rubber  
**LIFE:** Greater Than 10 Million Cycles  
**TRAVEL:** 0.055 in.  
**ACTUATION FORCE:** 7.05 oz. +/- 1.06oz (200g +/- 30g)  
**FEEDBACK:** Tactile with Mechanical Snap

## POWER

**PS2:**  
**KEYBOARD:** 200mA@5V (from Keyboard port)  
**POINTER:** 35mA@5V (from Mouse port)  
**USB:** 235mA@5V (from CPU port)

## TEMPERATURE RANGE

**STORAGE:** -40°F to +158°F (-40°C to +70°C)  
**OPERATING:** -4°F to +140°F (-20°C to +60°C)

## HUMIDITY

100% Humidity Resistant

## VIBRATION

**POWER SPECTRAL DENSITY:** .04g/HZ  
**FREQUENCY RANGE:** 20Hz-2Khz  
**DURATION OF TEST PER AXIS:** 3 hours

## SHOCK

3 X 11 ms pulses of 50g on each of 3 axis

## WEIGHT

1.75 lbs +/- 0.10 lbs (0.79 kg +/- 0.05 kg)

PROPRIETARY AND CONFIDENTIAL

SCALE: 1:2



iKey, Ltd.  
 2621 Ridgpoint Dr. Suite 235  
 Austin, Texas 78754

©2008 iKey, Ltd.

Voice: (512) 837-0283  
 Fax: (512) 927-8630

Part Number: SLP-86-911

Drawing Title: SLP-86-911-MKT

Drawing Number: MKT0099


Revision: 1.00

Sheet: 1 OF 2

Date: 12.09.08

JWB

# SLP-86-911 MOUNTING



PMU BEZEL: ABS/Polycarbonate with #4-40 x 0.75" Metal Studs (16 Places)

PROPRIETARY AND CONFIDENTIAL

SCALE: 1:2



iKey, Ltd.  
2621 Ridgpoint Dr. Suite 235  
Austin, Texas 78754

©2008 iKey, Ltd.  
Voice: (512) 837-0283  
Fax: (512) 927-8630

Part Number: SLP-86-911

Drawing Title: SLP-86-911-MKT

Drawing Number: MKT0099

Revision: 1.00

Sheet: 2 OF 2

Date: 12.09.08

JWB